

KATHON™ 893 MW Biocide

Metalworking Fluid Fungicide for Water-Based Cutting Fluids

EPA Reg. No.: 707-195

General

Soluble, synthetic, and semi-synthetic metalworking fluids or coolants provide an excellent environment for the growth of various microorganisms, including bacteria, mold, and yeast. If allowed to grow, these organisms can have detrimental effects on the fluids. For example, bacteria, which can grow very quickly, can destroy the integrity of the fluid by discoloration, destroying lubricity characteristics, and causing emulsions to split. Bacteria can also reduce the pH of the fluid, which can promote corrosion. Some forms of bacteria have objectionable odors. Fungi typically grow more slowly than bacteria, but can form large masses which clog filters and lines and in some cases lead to system shutdown; fungi also generate foul odors and can cause corrosion. The increased use of synthetic fluids over the past few years has led to an even greater need for the enhanced fungal control that KATHON™ 893 MW Biocide can provide.

For Tankside and Concentrate

KATHON™ 893 MW Biocide is a broad-spectrum fungicide that has been recommended and widely used for tankside control of fungi in metalworking central systems. KATHON 893 MW is also an effective fungicide for use in many metalworking fluid concentrates with the appropriate stabilizer package. Due to the wide variations in metalworking fluid formulations, laboratory or small-scale tests are recommended to evaluate KATHON 893 MW in usedilution and concentrate metalworking fluids before they are commercialized.

KATHON 893 MW is a highly effective, industrial fungicide that exhibits excellent fungistatic and fungicidal activity against fungi, including yeasts and mold, and Gram-Positive bacteria, and limited activity against Gram-Negative bacteria. Commonly known as octhilinone, 2-n-octyl-4-isothiazolin-3-one is the active ingredient of KATHON 893 MW. It is supplied as a 45 percent active liquid in propylene glycol.

The information in this brochure has been compiled to familiarize the reader with KATHON 893 MW technology, to communicate the tremendous benefits of this product, and to provide directions for safe and efficient use of the product. By following the precautions outlined in this brochure, on the product label, and on the Dow Safety Data Sheet (SDS), KATHON 893 MW can be safely handled.

Structure

$$\begin{array}{c|c}
H & C & O \\
 & C & N \\
 & C_3H_8^{-1}
\end{array}$$

2-n-octyl-4-isothiazolin-3-one 45% minimum Propylene glycol (inert) 50% minimum

Physical Properties

The following are typical properties of KATHON™ 893 MW Biocide; they are not to be considered product specifications.

Appearance:	Yellow to amber liquid
Color (VCS):	
Odor:	
Specific gravity @ 24°C:	1.03
Flash point, °C (Pensky Martens Closed Cup):	93
Viscosity Brookfield @ 20°C, cps:	40
Melting point, °C:	40
Boiling point, °C:	188
Vapor pressure, active ingredient @ 25°C:	

Solubility

The solubility data provided below were determined at ambient temperatures (20 to 25°C). The solubility and stability of the active ingredient may be affected when the temperature is lowered to 0°C or increased to 60°C.

- KATHON™ 893 MW Biocide is soluble in methanol, ethanol, propylene glycol, acetone, ethyl ether, ethyl acetate, chloroform, butyl Cellosolve, corn oil, and mineral oil.
- The solubility of KATHON 893 MW in toluene is 25% w/v.
- The solubility of KATHON 893 MW in water at 25°C is 480 ppm (active ingredient), although this may be increased by using suitable surfactants and emulsifiers.
- KATHON 893 MW is insoluble in heptane.

Compatibility

In concentrate and use-dilution metalworking fluids, the compatibility of KATHON™ 893 MW Biocide is concentration-dependent and varies from formulation to formulation. It is compatible with most metalworking fluid additives, including surfactants and amines. Compatibility with amines may vary by the type, concentration and pH. Strong reducing agents, such as sulfides, mercaptans, bisulfites and metabisulfites, or strong oxidizing agents, such as hypochlorites, may affect the efficacy of KATHON 893 MW. Laboratory or small-scale tests are recommended in order to evaluate KATHON 893 MW compatibility in use-dilution or concentrate metalworking fluids prior to commercialization.

KATHON 893 MW is compatible with most other metalworking fluid biocides, including KATHON 886 MW and KATHON CC (methylchlorosiothiazolone), KORDEK™ LX5000 (methylisothiazolone), ROCIMA™ BT 2S biocides (benzisothiazolone), triazine and formaldehyde-releasers, IPBC (iodopropynylbutylcarbamate) and sodium Pyrithione.

Stability

In-Use Stability: KATHON™ 893 MW Biocide has excellent stability in end use dilutions of metalworking fluids. It is stable over a wide pH range (4-10) in water and in metalworking fluid systems.

Concentrate Stability: KATHON™ 893 MW Biocide stability, in metalworking fluid concentrates, is variable. We recommend checking stability and performance before commercialization of products. Dow has several recommended stabilizers to improve stability and compatibility in many types of concentrates.

Storage Stability: In general, the storage stability of the KATHON™ 893 MW Biocide product is excellent. The shelf life of the product is nominally twelve years at 25°C. It is

strongly recommended, however, that both the stability and compatibility of KATHON™ 893 MW Biocide in metalworking fluid formulations or systems be thoroughly examined before commercialization.

Key Features & Benefits

Table 1

The many advantages of protecting your metalworking fluids with KATHON™ 893 MW Biocide fungicide include:

Features	Benefits
Highly effective microbicide	Extends metalworking fluid life, reduces downtime, reduces makeup fluid use and reduces fluid disposal costs
Broad spectrum activity	Kills fungi and prevents the return of slime caused by fungal microorganisms, eliminates clogged lines and filters and musty odors caused by fungi
Patented combinations of KATHON™ 886 MW or KORDEK™ LX5000 biocides with KATHON™ 893 MW Biocide	Synergistic combinations that enhance the already wide spectrum of bioactivity. Enhanced activity present even if KATHON 893 MW is added in the concentrate and KATHON 886 MW added tankside
Good temperature and pH stability	Works well in a variety of metalworking conditions up to 60°C (140°F) and pH 10
Highly soluble in water and does not foam	Easy to dose
Provides long lasting fungal control	Cost effective versus competitive tankside treatments
Fast acting	Quickly controls growth and activity of odor-causing fungi
Effective at low use rates and biodegradable	Better for the environment
Does not contain, release or generate formaldehyde	Not subject to concern about formaldehyde, a known carcinogen

Applications/ Directions for Use

Method of Addition

KATHON™ 893 MW Biocide should be directly dispensed into metalworking fluid concentrates or use-dilution metalworking fluids using a metering pump or other point-of-use device where possible and uniformLy dispersed throughout the fluid.

Fluid Concentrate

KATHON™ 893 MW Biocide should be added to metalworking fluid concentrates at a level that ensures the final use-dilution fluid will contain 55 to 167 ppm of product (25 to 75 ppm active ingredient). KATHON 893 MW stability in a given concentrate should be determined prior to commercialization. Contact your local Dow representative for assistance in selecting one of several recommended stabilizers to enhance the performance and compatibility of KATHON 893 MW in your metalworking fluid concentrate.

Use-Dilution Fluid

We highly recommend grossly contaminated systems be cleaned before treatment is begun.

Initial Dose: For a noticeably fouled system, add 0.47 to 1.44 lbs (7 to 21 fl oz) of KATHON™ 893 MW Biocide per 1,000 gallons of fluid. This will provide 25 to 75 ppm active ingredient. Repeat until control is achieved.

Subsequent Dose: For maintenance of a non-fouled system, add 0.09 to 0.58 lbs (1.3 to 8.6 fl oz) of KATHON™ 893 MW Biocide per 1,000 gallons of fluid every four weeks. This will provide 5 to 30 ppm active ingredient. A higher dose range and/or increased frequency of treatment may be required, depending upon the rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

Recommended Use Practices

General Practices When Using KATHON™ Biocides

- Know the size of your system and dose at the recommended use levels.
- To improve performance and longevity, add KATHON™ 893 MW Biocide on the clean side
 of the filters. It may be necessary to occasionally add KATHON 893 MW to the dirty side
 of the filters if large populations of microorganisms are detected there.
- Minimize contamination:
 - Eliminate or minimize dead spots
 - Disconnect unused portions of the system
 - Do not throw trash in sumps
- Always remember to triple rinse (or equivalent) empty containers to avoid incidental contact.
- Post placard with safety information and deactivation protocol near biocide handling area.

Maximizing the performance of KATHON™ 893 MW Biocide

Additional guidelines for maximizing the performance of KATHON™ 893 MW Biocide are as follows:

- KATHON 893 MW stability and performance is improved with lower pH. Whenever possible, maintain the pH of system below pH 9.2. Lower pH also makes amines and amine-containing compounds less aggressive.
- For systems with pH greater than 9.5, we strongly recommend determination of biological efficacy and chemical stability prior to use.
- Avoid adding highly basic additives (alkaline materials with pH of 10-12) immediately
 prior to or after adding KATHON 893 MW to your system. If a highly basic additive must
 be added, allow sufficient time (at least 30 minutes) between additions. Minimize levels
 of diethanolamine (DEA) in your system. If possible use 99% triethanolamine (TEA) or
 monoethanolamine (MEA) instead of DEA, and use these at as low a level as possible.
- Always add KATHON 893 MW directly to the metalworking fluid sump. Never use KATHON 893 MW in a spray bottle.
- Avoid charging KATHON 893 MW in high temperature zones, since increasing temperatures accelerate other degradation effects. Ideally, add KATHON 893 MW to the fluid below 60°C (140°F).
- Avoid adding KATHON 893 MW and incompatible corrosion inhibitors directly to the tank at the same time.

Performance Information

How Does KATHON™ 893 MW Biocide Work?

KATHON™ 893 MW Biocide utilizes a two-step mechanism involving rapid growth inhibition leading to a loss of cell viability. Growth inhibition is the result of rapid disruption of the central metabolic pathways of the cell by inhibition of several specific enzymes, including dehydrogenases. The critical enzymes which are affected are associated with the Krebs cycle, nutrient metabolism and energy generation.

The key physiological activities that are rapidly inhibited in microbial cells are respiration (oxygen consumption), energy generation (ATP synthesis), and growth (assimilation). Many of these key enzymes are present in both aerobic and anaerobic microorganisms, which explains why KATHON 893 MW is such a broad spectrum biocide.

Inhibition of cellular activity and growth is rapid (within minutes), whereas cell death (cidal activity) is observed after several hours' contact. In general, the higher the concentration of biocide, the shorter the contact time required for more complete kill.

Cell death results from the progressive loss of protein thiols in the cell from one of multiple pathways. As cell metabolism is disrupted, free radicals are produced which also results in cell death. This unique mechanism results in the broad spectrum of activity of KATHON™ 893 MW Biocide, low use levels for microbial control, and difficulty in attaining resistance by mutation. See technical bulletin (CS-632) for more detailed information.

How Rapidly Does KATHON™ 893 MW Biocide Work?

Within minutes after addition of KATHON™ 893 MW Biocide to a metalworking fluid sump, the metabolic activity of the microorganisms in the system shuts down. This includes cellular respiration (oxygen uptake), growth, energy generation, and nutrient uptake. The microorganisms, although still alive, are no longer able to reproduce or metabolize metalworking fluid components. After 24 to 48 hours of contact with a lethal dose of the biocide, most of the microorganisms have been killed.

How Long Does KATHON™ 893 MW Biocide Last?

KATHON™ 893 MW Biocide has excellent in-use stability and generally retains its antimicrobial efficacy in metalworking fluid systems for 2 to 4 weeks. Variables such as degree of fluid contamination, effectiveness of the filtration system, system turnover time, compatibility between the microbicide and the metalworking fluid components, and other system additives involved, can affect the life of the microbicide in a system.

Is KATHON™ 893 MW Biocide Effective in Reducing Fungal Biofilms?

YES. KATHON™ 893 MW Biocide has been shown to reduce microbial fouling and prevent biofilm development in metalworking fluid systems. The benefits of reduced fungal biofouling include improved system performance, reduced filter plugging, reduced biocorrosion, and improved microbial control.

Is KATHON™ 893 MW Biocide Effective When Used in Concentrates?

YES. KATHON™ 893 MW Biocide may be used in certain fluid concentrates to provide efficacy in the final use dilutions. Although KATHON 893 MW stability may not be suitable for all concentrates, we have had success with the biocide alone or in combination with one of our recommended stabilizers.

How Can I Improve KATHON™ 893 MW Biocide Stability in Concentrates?

We recommend testing KATHON™ 893 MW Biocide in concentrates prior to commercialization. Dow technical staff can assist you in formulating products. We have years of experience and a range of recommended stabilizers to prolong the lifetime and improve compatibility of KATHON 893 MW in concentrates. Contact your sales representative for assistance.

Efficacy Data

Anti-Microbial Properties of KATHON™ 893 MW Biocide

Initial determinations of the efficacy of any biocidal product are made via minimum inhibitory concentration (MIC) measurements. The MIC test yields valuable information about the product's inherent antimicrobial efficacy and spectrum of activity.

The MIC for any product is the lowest level at which the active ingredient inhibits the growth of various microorganisms. This method is a useful tool for screening antimicrobial agents

under standardized laboratory conditions, in nutrient-rich growth conditions. In interpreting the data, remember that low values correspond to high activity.

Table 2 indicates that KATHON™ 893 MW Biocide possesses outstanding antimicrobial activity against a broad range of fungi (both yeasts and molds). KATHON 893 MW has very low MIC values for most of the fungi tested and there is no gap in the spectrum of activity among the organisms tested.

Table 2 Fungistatic Activity of KATHON™ 893 MW Biocide

Organism	ATCC Number (Strain)	MIC* in PPM Active Ingredient
Alternaria dianthicola	11782	1
Aspergillus niger	9642	8
Aspergillus oryzae	10196	2
Aspergillus repens	9294	2
Aureobasidium pullulans	9348	0.3
Candida albicans (yeast)	11651	2
Chaetomium globosum	6205	4
Cladosporium resinae	11274	0.5
Lenzites lepideus	12653	2
Lenzites trabea	11539	2
Penicillium funiculosum	9644	1
Phoma glomerata	6735	<1.0
Phoma pigmentivora	12569	2
Rhizopus stolonifer	10404	4
Rhodotorula rubra (yeast)	9449	4
Saccharomyces cerevisiae (yeast)	2601	1
Trichophyton interdigitale (mentagrophytes)	9533	<1.0

^{*}Fungistatic minimum (MIC) are based on active ingredient (AI) as determined in twofold broth serial dilution tests.

The data are intended only to indicate the activity of KATHON 893 MW in an aqueous solution; they do not represent recommended use levels. Moreover, the microorganisms on the list are not all the ones involved in the deterioration of metalworking fluids.

Short Term Study

KATHON™ 893 MW Biocide was evaluated as a tankside fungicide in a wide variety of metalworking fluids, including synthetics, semi-synthetics, and soluble-oil fluids. In a one-week eradication study described below, a total of 16 fluids from various manufacturers in the United States, Europe, and Japan were tested.

Table 3 provides test results for several of these fluids.

Table 3
Comparative Fungicidal activity of KATHON™ 893 MW Biocide and Sodium Pyrithione (one week education study)

Fungi, CFU/mL				
Biocide	Concentration (PPM Active)	Synthetic	Semi-Synthetic	Soluble-Oil
TIME ZERO		5,000	500	120,000
Control None	45,000	1,000	15,000	
	5	<1	25	13,000
	10	<1	20	11,000
	25	<1	<1	80
KATHON™ 893 MW Biocide	50	<1	<1	<1
	75	<1	<1	<1
	100	<1	<1	<1
	50	9,000	15	20,000
Sodium Pyrithione	100	4,000	20	10,000

Preparation of Individual Fungal Inoculum

Each fluid was diluted 50:1 with tap water, set up in a 1-liter (L) French square bottle, and inoculated with spore scrapings of various metalworking fluid fungal isolates. Each 1-L setup was constantly aerated to promote a fungal count of approximately 103 to 104. Thus, each fluid type developed a population that was adapted to growth in that particular medium.

Test Procedure

The actual test systems were run in volumes of 50 mL, which consisted of 40 mL of virgin metalworking fluid (generally diluted 20:1) and 10 mL of the adapted inoculum as described above. Prior to inoculation, the fluids containing fungal growth were blended for two minutes at high speed in a Waring blender. Most samples contained 0.5 g of iron filings. At time zero, the following active levels of KATHON™ 893 MW Biocide were added: 5 ppm, 10 ppm, 25 ppm, 50 ppm, 75 ppm, and 100 ppm. Additionally, samples were run containing 50 ppm and 100 ppm active sodium Pyrithione. Once fluids were dosed with biocide and inoculated, they were mechanically shaken for one week and plated on sabouraud dextrose agar.

Results

KATHON™ 893 MW Biocide was completely effective in all fluids at levels ranging from 5 to 75 ppm active ingredient. In all but one of the fluids, it was effective at concentrations in the range of 5 to 50 ppm active ingredient. In synthetic fluids, which are prone to fungal growth, KATHON 893 MW was effective in the range of 5 to 10 ppm. Sodium Pyrithione was not very effective at recommended use levels of 50 to 100 ppm active ingredient.

Long-term Study

A long-term study was done to compare the fungicidal activity of KATHON™ 893 MW Biocide and sodium Pyrithione in a synthetic metalworking fluid, use-dilution 1:30. The concentration of KATHON 893 MW studied ranged from 10 to 75 ppm active ingredient and the concentration of sodium pyrithione ranged from 50 to 200 ppm active ingredient.

Test Procedure

The test samples were inoculated at zero time and again every two weeks with fungal inoculum isolated from naturally contaminated synthetic metalworking fluid and maintained in the same fluid employed in the test.

Results

Results, provided in Table 4, show that particularly high fungal counts were not achieved in the untreated control for this particular fluid (note: Due to the inherent mycelial clumping common to most fungal species when growing in liquid substrates, plate counts of colony-forming units carried out on the aliquots of the liquid are not always indicative of the degree of fungal contamination present). In spite of this, sodium Pyrithione allowed fungal survival at all levels at which it was tested. KATHON™ 893 MW Biocide, however, exhibited complete fungal control at significantly lower levels.

Table 4
Comparative Fungicidal Activity of KATHON™ 893 MW Biocide and Sodium Pyrithione in a Synthetic Metalworking Fluid (1:30)

Fungi, CFU/mL				
Biocide	Concentration (PPM Active)	2 Weeks	4 Weeks	6 Weeks
Control	None	500	6,900	7,000
	0	<10	<10	<10
KATHON™ 893 MW Biocide	25	<10	<10	<10
	50	<10	<10	<10
	75	<10	<10	<10
	50	30	20	460
	75	80	40	590
Sodium	100	120	40	340
	150	230	240	620
	200	130	50	600

Biocide Combination

There is usually a need to control both bacteria and fungi in metalworking fluid systems. Bacteria and fungi, however, are not always controlled by one biocide. For example, KATHON™ 886 MW Biocide is a broad-spectrum biocide that controls the growth of bacteria and fungi, including molds and yeast, in many metalworking fluid systems and therefore can usually be used alone. Some fluids, however, contain aggressive components which may decrease the stability of KATHON 886 MW and therefore reduce its efficacy for controlling microorganisms. If such fluids are especially prone to fungal growth, use of KATHON 893 MW in conjunction with KATHON 886 MW, KORDEK™ LX5000, or ROCIMA™ BT 2S biocides is recommended. These products are completely compatible and provide excellent cost performance.

KATHON 893 MW is also compatible with other bactericides, including triazine and formaldehyde releasers, and other fungicides. The use of KATHON 893 MW in the same system as KATHON 886 MW, KORDEK LX5000, and a number of other biocides are covered in several Dow patents.

Field Trial Data

The efficacy of KATHON™ 893 MW Biocide in a use-dilution synthetic metalworking fluid was evaluated under actual use conditions during a five-month field trial in a 200,000-gallon system. At the start of the trial, fungal mats covered the walls of the flumes and weirs of the system and filters which required constant maintenance to prevent clogging (see Figure 1). Fungal slime was also present on and around many of the machines supplied by the system. The bacterial population of the fluid was between 103 and 104 cfu/mL (colony-forming units per mL), and the fungal population was between 380 and 790 cfu/mL.

During the first 45 days of the trial, the level of KATHON™ 893 MW Biocide was maintained at approximately 25 ppm active ingredient. For the remaining 3 months of the trial, the level of KATHON 893 MW was maintained between 30 ppm and 10 ppm active ingredient.


The results of the trial showed that the regimen of KATHON 893 MW addition chosen provided essentially complete control of fungal organisms in the fluid itself and also destroyed the fungal organisms comprising the mats covering the walls of the flumes and weirs of the system. These fungal mats lost their integrity and gradually sloughed off the surfaces to which they were attached (see Figure 2). The microbial slime present on and around the machines also disappeared. The bacterial populations of the fluid remained in the range of 102 to 104 cfu/mL, throughout the trial. In addition, the amount of makeup fluid required to maintain the desired characteristics of the fluid was reduced significantly (42 percent) during the trial.

Figure 1:

Dark-colored bioslime growing on the weirs and flumes of a metalworking fluid system.

Figure 2:

The same metalworking fluid system after treatment with KATHON™ 893 MW Biocide.



Toxicology, Environmental Hazard and First Aid

For product safety information, refer to the Safety Data Sheet (SDS).

Safe Handling and Storage

Handling

The procedures used for handling concentrated biocide solutions are similar to those used for handling concentrated acids and alkalis. The purpose is to prevent all eye and skin contact, including inhalation of mists, and thereby prevent possible injury and sensitization.

Personnel handling KATHON™ 893 MW Biocide as supplied should always wear protective clothing, which includes chemical splash goggles, an impervious apron or rain suit, and impervious rubber gloves. We recommend that employees working with KATHON 893 MW as supplied thoroughly wash with soap and water at the end of a shift or prior to eating, drinking, smoking, or applying cosmetics. Special care should be taken to avoid contamination of surfaces or materials that may later be handled by unprotected personnel, for example, door and tap handles.

Storage

KATHON™ 893 MW Biocide is packaged in polyethylene or polyethylene-lined containers. It should not be stored in unlined metal containers since it is a corrosive material. Normal recommended storage temperatures are in the range of 10° to 25°C (50° to 80°F). Shelf life ~12 years (packaging should be evaluated and replaced as needed for transport compliance over the duration of product shelf life). Storage at >120°F for extended periods of time can result in degradation of the active ingredient.

Store away from direct sunlight.

Decontamination and Spill Procedures

Decontamination Solutions

KATHON™ 893 MW Biocide can be decontaminated with a 5% solution of sodium hypochlorite (NaOCI) containing 2-5% sodium bicarbonate (NaHCO₃). Solutions should be freshly prepared. Employees preparing or handling decontamination solutions should wear chemical splash goggles, an impervious apron or rain suit, and impervious rubber gloves.

Note: Do not use decontamination solution to treat skin, eyes or clothing which have come in contact with KATHON 893 MW.

Decontamination of Equipment

Equipment used in the handling of KATHON™ 893 MW Biocide, such as mix tanks, lines, pumps, etc., must be decontaminated before carrying out maintenance or used for other service. To decontaminate this equipment, estimate the volume of KATHON 893 MW remaining in the well-drained system. Prepare 10 volumes of decontamination solution per volume of KATHON 893 MW (45%) and circulate the mixture throughout the equipment. Be certain that the KATHON 893 MW and decontamination solution mix well. Wait at least 30 minutes to ensure complete reaction. Drain and rinse with clean water or detergent solution. Decontamination solution runoffs should be drained to a chemical sewer unless prohibited by state or local regulations.

Drips, minor spills and exposed wet areas should be cleaned up promptly with the hypochlorite/bicarbonate mixture. Contaminated surfaces should be swabbed with decontamination solution and allowed to stand for 30 minutes before rinsing thoroughly with water. Decontaminated solutions should be drained to a chemical sewer unless prohibited by state or local regulations.

Note: Because of the high level of activity of KATHON 893 MW, a relatively small quantity could have a damaging impact on the effectiveness of waste treatment bio-systems. Laboratory or plant spills should be decontaminated with decontamination solution before being released to a biological waste treatment system.

Cleanup of Spills

Procedures provided in the Safe Handling Section should be followed when cleaning spills of KATHON™ 893 MW Biocide.

- 1. Wear impervious rubber gloves, chemical splash goggles, protective clothing and overshoes.
- Dike and adsorb the spilled material on an inert solid, such as clay or vermiculite or with spill control pillows.
- Transfer the adsorbent or pillows and surrounding surface soil into a pail or drum. This container should be no more than two-thirds full.
- Treat the contents of the container with 10 volumes of decontamination solution per estimated volume of spilled KATHON 893 MW.
- Treat the surrounding spill area with excess decontamination solution. Flush after a minimum of 30 minutes into a chemical sewer.
- Do not discharge spills and cleaning runoffs into open bodies of water, because of a potential adverse impact on the environment.
- 7. Carefully remove the contaminated gloves and place them in the container (peel off the gloves by pulling on the outside of the glove sleeve turning them inside out as they are removed). After 48 hours, seal the container and dispose of it by landfilling in accordance with local, state, and federal regulations.

Analytical Information

Bulletin CS-561, which is available on request, contains methods for determining the presence of KATHON™ 893 MW Biocide's active ingredient in use dilution metalworking fluids by high performance liquid chromatography (HPLC). This bulletin also contains HPLC procedures for determining KATHON 886 MW active ingredients in use-dilution metalworking fluids.

Safety Data Sheets

Dow maintains Safety Data Sheets (SDS) for all of its products. These sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products. We recommend that you obtain and review Safety Data Sheets (SDS) for our products from your distributor or Dow technical representative before using our products in your facility. We also suggest that you contact your supplier of other materials recommended for use with our product for appropriate health and safety precautions before using them.

Dow Technical Support

Dow Sales Service and Technical Service departments have over twenty-five years' experience evaluating KATHON™ biocides' performance in a variety of applications. In the area of metalworking fluids we can advise on determining KATHON biocide stability and efficacy in use-dilution as well as concentrate metalworking fluids, and we can make recommendations on how to evaluate the level and type of system contamination you may be experiencing. In addition, Dow personnel can assist you with questions on KATHON biocides' toxicology, environmental issues, safe storage, handling and use. Finally, Dow has available for your use a videotape on the safe use and handling of the family of KATHON and KORDEK™ biocides for the metalworking industry, including KATHON 893 MW, KATHON 886 MW and KORDEK LX5000 biocides.

For further information, contact your local Dow KATHON biocide representative or contact Dow.

Shipping Information

KATHON™ 893 MW Biocide 45% solution is available in 5-gallon pails (44 lbs), 30-gallon drums (44 lbs), and cartons (22 lbs) containing two 1-gallon jugs.

To obtain samples, technical assistance, a Safety Data Sheet (SDS), or to have a technical representative call for an appointment, contact the nearest Dow office.

Biocidal Product Directive Compliance

KATHON™ 893 MW Biocide is a biocidal product intended for use in accordance with Product Type 13 (Metalworking fluid preservatives) of the Biocidal Products Directive 98/8/EC (BPD).

Product Stewardship

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products – from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

For further information visit our website: www.dowmicrobialcontrol.com or call:

Central and Eastern Europe:

Turkey +90-216-571-16-00

Russia +7-495-663-78-20

Poland +48-22-543-18-00

Western Europe:

+800-3-694-6367 (toll-free)

+31-115-67-26-26 (phone)

+31-115-67-28-28 (fax)

North America:

+1-800-447-4369 (toll-free)

+1-989-832-1560 (phone)

+1-989-832-1465 (fax)

Middle East and Africa:

UAE +971-4-332-88-66

South Africa +800-99-5078 (toll-free)

Greater China:

Shanghai +86-21-3851-1000

Beijing +86-10-8527-9199

Guangzhou +86-20-3813-0600

Taiwan +886-227-718-000

Southeast Asia:

Philippines +63-2-867-3293

Indonesia +62-21-2995-6273

Singapore +65-6830-4575

+65-6796-6217 Thailand +66-2365-7371

Vietnam +84-8-3822-5808 Malaysia +603-7965-5200

Australia and New Zealand:

+613-9226-3500 (phone)

+61-3-9226-3562 (fax)

Japan and Korea:

Japan +81-3-5460-2261

Korea +82-2-3490-4348

Indian Subcontinent: +91-22-6793-4953 (phone)

+91-22-6793-4924 (fax)

Latin America:

+55-11-5188-9555 (phone)

+55-11-5188-9400 (fax) Other Global Areas:

+1-989-832-1560 (phone)

+1-989-832-1465 (fax)

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

USE BIOCIDES SAFELY. ALWAYS READ THE LABEL AND PRODUCT INFORMATION BEFORE USE.

