



AMBERLITE™ RF14

Industrial Grade Inert Polymer

Introduction

AMBERLITE RF14 resin is an inert polymer with a specific gravity lower than that of water. It has been developed for use as an upper layer in upflow operated ion exchange systems, such as floating beds. The suffix RF means "Reverse-flow".

Properties

Physical form	Colourless, translucent uniform cylinders
Matrix	Polypropylene
Specific gravity	0.90
Shipping weight	500 to 580 g/L
Particle size	Diameter: 1.2 to 1.5 mm Length: 1.3 to 1.7 mm
Physical characteristics	Hard, attrition resistant

Suggested Operating Conditions

Maximum operating temperature	100°C
Minimum bed depth	150 mm

Applications

Typical uses for AMBERLITE RF14 resin are as follows:

1. Floating beds, totally or partially compacted, with upflow service run.
2. Conventional beds, with downflow service and upflow regeneration.

In both cases, AMBERLITE RF14 resin is used as an upper layer to prevent the finer active resin from blocking the strainers. This layer also improves the distribution or collection of water or regenerant above the resin bed.

Limits of use

AMBERLITE RF14 resin is suitable for industrial uses. For other specific applications such as pharmaceutical, food processing or potable water applications, it is recommended that all potential users seek advice from Rohm and Haas in order to determine the best resin choice and optimum operating conditions.

For more information about DOW™ resins, call the Dow Water & Process Solutions business:

North America: 1-800-447-4369
 Latin America: (+55) 11-5188-9222
 Europe: +800-3-694-6367
 Italy: +800-783-825
 South Africa: +0800 99 5078
 Pacific: +8007776 7776
 China: +400 889-0789

<http://www.dowwaterandprocess.com>

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

