

**DOWTHERM™ A****Product Type** Synthetic organic heat transfer fluid – Liquid and Vapor Phase Data**Applications**

- Indirect heat transfer

Recommended Use Liquid phase: 15°C (60°F) to 400°C (750°F)
Vapor phase: 257°C (495°F) to 400°C (750°F)**Temperature Range****Description** DOWTHERM™ A heat transfer fluid is a eutectic mixture of two very stable compounds, biphenyl (C₁₂H₁₀) and (C₁₂H₁₀O). These compounds have practically the same vapor pressures, so the mixture can be handled as if it were a single compound. DOWTHERM A fluid may be used in systems employing either liquid phase or vapor phase heating.**Typical Properties†**

Composition		
Diphenyl Oxide/Biphenyl Blend		
Color	Clear to light yellow	
Property	SI Units	English Units
Freeze Point	12.0°C	53.6°F
Atmospheric Boiling Point	257.1°C	494.8°F
Flash Point ¹	113°C	236°F
Fire Point ²	118°C	245°F
Autoignition Temperature ³	599°C	1110°F
Density at 25°C (75°F)	1056 kg/m ³	66.0 lb./ft. ³
Surface Tension in Air at:		
20°C (68°F)	40.1 Dynes/cm	40.1 Dynes/cm
40°C (104°F)	37.6 Dynes/cm	37.6 Dynes/cm
60°C (140°F)	35.7 Dynes/cm	35.7 Dynes/cm
Estimated Critical Temperature	497°C	927°F
Estimated Critical Pressure	31.34 bar	30.93 atm
Estimated Critical Volume	3.17 l/kg	0.0508 ft. ³ /lb.
Average Molecular Weight		166.0
Heat of Combustion	36,053 kJ/kg	15,500 Btu/lb.

†Not to be construed as specifications.

¹SETA²C.O.C.³ASTM E659-78

Saturated Liquid Properties of DOWTHERM™ A Fluid (English Units)

Temperature °F	Specific Heat Btu/lb. °F	Density lb./ft. ³	Thermal Conductivity Btu/hr. ft. ² (°F/ft.)	Viscosity (cP)	Vapor Pressure (psia)
60	0.373	66.37	0.0805	4.91	0.000
120	0.396	64.72	0.0775	2.12	0.003
180	0.418	63.03	0.0744	1.22	0.028
240	0.441	61.30	0.0713	0.81	0.16
300	0.463	59.51	0.0682	0.59	0.64
360	0.485	57.65	0.0651	0.45	2.03
420	0.507	55.72	0.0620	0.35	5.38
480	0.529	53.70	0.0590	0.28	12.25
540	0.552	51.57	0.0559	0.23	24.72
600	0.575	49.29	0.0528	0.19	45.31
660	0.599	46.82	0.0497	0.16	76.89
720	0.627	44.08	0.0466	0.14	122.7
780	0.665	40.93	0.0436	0.12	186.4

Saturated Liquid Properties of DOWTHERM™ A Fluid (SI Units)

Temperature °C	Specific Heat kJ/kg K	Density kg/m ³	Thermal Conductivity W/mK	Viscosity mPa sec	Vapor Pressure (bar)
15	1.558	1063.5	0.1395	5.00	0.00
65	1.701	1023.7	0.1315	1.58	0.00
105	1.814	990.7	0.1251	0.91	0.01
155	1.954	947.8	0.1171	0.56	0.06
205	2.093	902.5	0.1091	0.38	0.28
255	2.231	854.0	0.1011	0.27	0.97
305	2.373	801.3	0.0931	0.20	2.60
355	2.527	742.3	0.0851	0.16	5.80
405	2.725	672.5	0.0771	0.12	11.32

Saturated Vapor Properties of DOWTHERM™ A Fluid (English Units)

Temperature °F	Vapor Pressure (psia)	Liquid Enthalpy Btu/lb.	Latent Heat Btu/lb.	Vapor Enthalpy Btu/lb.	Vapor Density lb./ft. ³	Vapor Viscosity cP	Vapor Thermal Cond. Btu/hr. ft. ² (°F/ft.)	Z _{vapor}	Specific Heat (c _p) Btu/lb. °F	Ratio of Specific Heats c _p /c _v
60	0.000	2.5	175.1	177.6		0.0054	0.0044	1.000	0.250	1.050
120	0.003	26.2	167.3	193.5		0.0060	0.0055	1.000	0.279	1.045
300	0.64	103.0	148.0	251.1	0.0130	0.0079	0.0092	0.996	0.361	1.035
360	2.03	131.1	142.0	273.1	0.0388	0.0086	0.0106	0.989	0.385	1.034
420	5.38	160.6	135.8	296.3	0.0967	0.0092	0.0120	0.977	0.409	1.034
480	12.25	191.4	129.2	320.5	0.2100	0.0098	0.0135	0.959	0.433	1.035
540	24.72	223.5	122.1	345.5	0.4102	0.0105	0.0150	0.932	0.456	1.039
600	45.31	256.9	114.2	371.1	0.7389	0.0166	0.0166	0.895	0.480	1.045
660	76.89	291.7	105.3	397.0	1.254	0.0183	0.0183	0.848	0.505	1.055
720	122.7	327.9	95.0	422.9	2.045	0.0200	0.0200	0.789	0.534	1.073
780	186.4	365.9	82.5	448.4	3.270	0.0219	0.0219	0.714	0.571	1.108

Saturated Vapor Properties of DOWTHERM™ A Fluid (SI Units)

Temperature °F	Vapor Pressure (bar)	Liquid Enthalpy kJ/kg	Latent Heat kJ/kg	Vapor Enthalpy kJ/kg	Vapor Density Kg/m ³	Vapor Viscosity mPa•s	Vapor Thermal Cond. W/mK	Z _{vapor}	Specific Heat (c _p) kJ/kg K	Ratio of Specific Heats c _p /c _v
15	0.00	4.9	407.2	412.1		0.0054	0.0075	1.000	1.044	1.050
65	0.00	88.1	380.9	469.4	0.0040	0.0063	0.0104	1.000	1.227	1.043
105	0.01	158.1	362.7	520.9	0.0341	0.0071	0.0129	0.999	1.366	1.038
155	0.06	251.2	341.5	592.7	0.2583	0.0080	0.0163	0.995	1.528	1.035
205	0.28	351.2	320.2	671.5	1.179	0.0090	0.0200	0.982	1.681	1.034
255	0.97	458.2	297.4	755.6	3.831	0.0100	0.0238	0.954	1.829	1.036
305	2.60	572.2	271.5	843.6	9.896	0.0110	0.0279	0.908	1.976	1.042
355	5.80	693.1	240.6	933.8	22.03	0.0122	0.0322	0.838	2.133	1.057
405	11.32	822.0	201.7	1023.7	45.17	0.0138	0.0368	0.740	2.333	1.094

Product Stewardship

The Dow Chemical Company and its subsidiaries (“Dow”) has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products—from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Safety Considerations

Material Safety Data (MSD) sheets are available from The Dow Chemical Company. MSD sheets are provided to help customers satisfy their own handling, safety and disposal needs and those that may be required by locally applicable health and safety regulations. MSD sheets are updated regularly, therefore, please request and review the most current MSD sheet before handling or using any product. These are available from the nearest Dow sales office.

Customer Notice

Dow encourages its customers to review their application of Dow products from the standpoint of human health and environmental quality. To help ensure that Dow products are not used in ways for which they were not intended or tested, Dow personnel will assist customers in dealing with ecological and products safety. Your Dow sales representative can arrange the proper contacts.

Contact information:

For more information about this product please call The Dow Chemical Company.

North America: +1 (800) 447-4369
 Latin America: +55 (115) 184-8722
 Europe: +3 (111) 567-2626
 Asia/Pacific: +6 (037) 965-5392
<http://www.dowtherm.com>

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to “Dow” or the “Company” mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

